



**Application: Application: Aplicación:**

Mercedes-Benz 300CE, 300D, 300E, 300TE, 400E, 500E, E300, E320, E420, E500



Fig 1



Fig 2



Fig 3




Fig 4

Fig 5a



Fig 5b



Fig 6



Fig 7



Fig 8



Fig 9




Fig 10




Fig 11




Fig 12



Fig 13




Fig 14




Fig 15



Fig 16



Fig 17



**Location of filter:** Under the cowl in the center of the vehicle.

**Tools:** Phillips-head screwdriver; 10mm wrench

**To remove existing filter:**

1. Open the hood. (Fig 1)
2. Pull back the rubber seal at the bottom of the windshield to the windshield wiper. (Fig 2)
3. Pull back the weather strip that lines the bottom of the cowl. (Fig 3)
4. Pull back the weather strip that lines the top of the engine compartment. (Fig 4)
5. Remove the section at the top of the engine compartment by unclipping it on both sides. (Fig 5a and Fig 5b)
6. Remove the two screws from the right-most cowl section. (Fig 6)
7. Remove the cowl section by pivoting it towards the outside of the vehicle. (Fig 7)
8. Remove the two screws from the cowl section to the right of the windshield wiper. (Fig 8)
9. Remove the screw under the windshield wiper. (Fig 9)
10. Remove the cowl section. (Fig 10)
11. Unhook the clip to the right of the filter.
12. Remove the first old filter by sliding it straight out of the housing. (Fig 11)
13. Slide the second filter down to remove it from the housing.
14. Remove the air vent on the opposite side of the windshield wiper by removing the 10mm bolt. (Fig 12 and Fig 13)
15. When installing the filter, the two hooks and ridges should be facing one another. These filters hook together when installed correctly. (Fig 14 and Fig 15)
16. Install your first new filter and slide it up. (Fig 16)
17. Install your second new filter into the housing and make sure the filters hook together. (Fig 17)
18. Re-hook the clip to the right of the filter.